



# TYPE APPROVAL CERTIFICATE

Certificate no.:  
**TAA0000023**  
Revision No:  
**4**

**This is to certify:**  
**that the Generator Automation System**

with type designation(s)  
**ECU 100 / GCU 100**

issued to  
**DEIF A/S**  
**Skive, Denmark**

is found to comply with  
**DNV rules for classification – Ships, offshore units, and high speed and light craft**

## Application:

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.**

## Location classes:

Temperature	B
Humidity	B
Vibration	A
EMC	A
Enclosure	Required protection according to relevant rules shall be provided upon installation on board

Issued at **Høvik** on **2025-10-25**

This Certificate is valid until **2027-02-12**.

DNV local unit: **Denmark CMC**

Approval Engineer: **Krzysztof Aleksander Jankowski**



for **DNV**

This document has been digitally signed and will  
therefore not have handwritten signature

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.  
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

## Place of system modules manufacture

DEIF A/S  
Skive  
Denmark

## Product description

The ECU 100 and GCU 100 series of products (ECU110, GCU111, GCU112, GCU113) are built for basic control and monitoring of marine engines and control, monitoring and protection of generators.

The variants and functions covered by this type approval				
Function	ECU 110	GCU 111	GCU 112	GCU 113
Engine start/stop	X	X	X	X
Engine monitoring	X	X	X	X
CANbus engine communication, J1939	X	X	X	X
Modbus communication, RS485	X	X	X	X
Programmable logic, M-logic	X	X	X	X
Remote annunciator support, AOP-2	X	X	X	X
Multiple language support	X	X	X	X
Event and alarm log	X	X	X	X
Integrated emulation software	X	X	X	X
Generator monitoring and protection		X	X	X
Breaker control			X	X
Emergency genset control				X

The ECU/GCU is intended for the following engine types	
Engine manufacturer	Engine controller / type
Caterpillar	ADEM III and A4/C4.4, C6.6, C9, C15, C18, C32
Cummins	CM850/570/2150/2250, QSL, QSB5, QXL15 and 7, QSM11, QSK19, 50 and 60
Detroit Diesel	DDEC III and IV/Series 50, 60 and 2000
Deutz	EMR3, EMR 2 (EMR)/912, 913, 914 and L2011
Iveco	EDC7 (Bosch MS6.2)/Series NEF, CURSOR and VECTOR 8
John Deere	JDEC/PowerTech M, E and Plus
MTU	MDEC, module M.302 or M.303/Series 2000 and 4000
MTU	MDEC, module M.201 or M.304/Series 2000 and 4000
MTU	ADEC/Series 2000 and 4000 (ECU7)
MTU	J1939 Smart Connect/Series 1600 (ECU8)
Perkins	Series 1100, 1300, 2300, 2500 and 2800
Scania	EMS
Scania	EMS S6 (KWP2000)/Dx9x, Dx12x, Dx16x
Volvo Penta	EDC4
Volvo Penta	EMS
Volvo Penta	EMS 2 and EDCIII/D6, D7, D9, D12 and D16 (GE and AUX variants only)

The following alarm and protection functions as defined by ANSI are available in the GCU units		
Protection function	ANSI	Levels
Generator reverse power	32R	2 steps
Generator over-current	50	2 steps
Fast over-current	51	2 steps
Generator over-voltage	59	2 steps
Generator under-voltage	27	2 steps
Generator over-frequency	81O	2 steps
Generator under-frequency	81U	2 steps
Busbar over-voltage	59B	2 steps
Busbar under-voltage	27B	2 steps
Busbar over-frequency	81O	2 steps
Busbar under-frequency	81U	2 steps
Generator overload	51	2 steps

The following alarm and protection functions as defined by ANSI are available in the GCU units		
Protection function	ANSI	Levels
Current unbalance	46	1 step
Voltage unbalance	60	1 step
Over-excitation	24	1 step
Loss of excitation	40	1 step

Software version
1.0x.x.
x - Shall be represented by fix digit. Changes shall be submitted to DNV for evaluation.

## Application/Limitation

1. The Type Approval is valid for systems made by production facilities listed under Place of Manufacture
2. The Type Approval covers hardware and software listed under Product description.
3. When GCU 100 is used for emergency generator application, factory settings for trip functions shall be modified so as to comply with requirements for protective functions of emergency generator sets in Pt.4 Ch.8 Sec.2 [3.3.2].
4. Engine control and monitoring points list are not in scope of this Type Approval and shall be checked in each case during approval of relevant documentation for engine control and monitoring system.
5. The Type Approval does not cover functionality of M-Logic. Any functions implemented in M-Logic shall be documented. If functions affect rule requirements, certification will be required according to Pt.4 Ch.9 Sec.1 [1.4].

### Documentation requirement:

For each delivery where the product is included the following information related to the application system is to be submitted for approval:

- Reference to this type approval certificate
- System block diagram/single line diagram including power supply arrangement and all communication lines / interfaces to other systems/locations
- Functional description, describing overall application and functionality, any implemented M-logic, any parameter which is not according to default setting
- Project-specific list of ANSI protection functions from the table above (with proposed limits and time delays) in addition to functions provided through the AOP(s) if applicable
- Test program for certification

### Product certificate

Each delivery of the application system **is to be** certified according to Pt.4 Ch.9 Sec.1. The Certification is to be performed at the manufacturer before the system is shipped to the yard. After certification the clause for software control will be put into force.

### Software update notification

When the type approved software is revised (affecting all future deliveries) DNV is to be informed by forwarding updated software version documentation. If the changes are judged to affect functionality for which rule requirements apply a new functional type test may be required and the certificate may have to be renewed to identify the new software version.

## Type Approval documentation

Declaration of conformity, 4910290091/A

Data sheet ECU 100, 4921240427/D

Data sheet GCU 100, 4921240428/D

ECU 100 and GCU 100 DEIF Type Certificate, 41240300073/A

Communication protocol ECU 100/GCU 100, 4189340804/A

Communication protocol for Modbus ECU 100/GCU 100, 4189340803/A

Parameter list ECU 100 and GCU 100, 4189340796/A

Functional description of option X3, AOP-2, 4189340484/G

Type test report, IPA0358-02

Type test summary report, IPA0358-02 dated 2013-09-10

Performance test summary IEC 60255, printed 13-09-04

Software Performance tests

Software release checklist ECU 1.00.0, IPD/CP no 424058, dated 14-04-30

Software release checklist GCU 1.00.0, IPD/CP no 424058, dated 14-04-30

IEC 60255 Performance test, dated 13-02-36

IEC 60255 Performance test, alarm response time test, dated 14-03-18  
IEC 60255 Performance test, setpoint accuracy on voltage generator low, dated 14-03-18  
IEC 60255 Performance test, setpoint accuracy on voltage generator high, dated 14-03-18  
ECU/GCU 100 Witness Test Report, dated 14-04-30  
02B RF electromagnetic field immunity test (to 6 GHz), 4910217502/N, dated 2020-08-07  
16A Radiated emission test (to 6 GHz), 4910216501/M, dated 2020-08-07

Designers reference handbook ECU 100, 4189340795/A  
Designers reference handbook GCU 100, 4189340798/A  
Operators manual ECU 100, 4189340797/A  
Operators manual GCU 100, 4189340800/A  
Installation instructions ECU 100, 4189340802/A  
Installation instructions GCU 100, 4189340799/A

Type approval renewal assessment report for TAA0000023, DNV Denmark CMC dated 2025-09-15

### Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021.  
Applicable tests according to IEC 60255-127/151.  
Functional Type Tests on a representative system with one emergency generator/bus at DEIF's test bench, dated 2014-04-30.

### Marking of product

On front side of product, the product is marked as either "ECU 100" or "GCU 100". On rear side of product, the variant is identified as "Type", e.g. GCU 113.

### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

A renewal assessment will be performed at renewal of the certificate.

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE