

IOM3.2

Input/output module

Data sheet

4921240640-C



Improve
Tomorrow



1. Series 300

1.1 About the hardware modules.....	3
-------------------------------------	----------

2. Technical specifications

2.1 Input/output module IOM3.2.....	4
-------------------------------------	----------

3. Legal information


3.1 Disclaimer and copyright.....	7
-----------------------------------	----------

1. Series 300


1.1 About the hardware modules

The hardware modules are printed circuit boards that slot in to either a rack R7.1 or rack R4.1. Depending on the type of module, they can provide AC or other measurements, inputs, outputs and give communication indication.

Example rack R7.1



Example rack R4.1



The hardware modules feature:

- Placement flexibility in the rack.
- Add, replace, or remove on-site.
- Automatically recognised.
- Configurable input and output functions (digital and analogue where applicable).

All slots must be covered during operation and blind modules can be used to cover unused slots.







2. Technical specifications

2.1 Input/output module IOM3.2



The input output module has 4 relay outputs, 4 analogue multifunctional outputs (including 2 pulse width modulation PWM outputs), 4 digital inputs, and 4 analogue multifunctional inputs. These I/Os are all configurable.




Internal cold junction compensation is not available on IOM3.2

IOM3.2 terminals

Module	Count	Symbol	Type	Name
	4		Relay output	Configurable
	2		Analogue multifunctional output (mA, V DC, PWM)	Configurable
	2		Analogue multifunctional output (mA, V DC)	Configurable
	4		Digital input	Configurable
	4		Analogue multifunctional input (mA, V DC, RMI)	Configurable

IOM3.2 technical specifications

Category	Specification
Relay outputs 	Relay type: Solidstate relay Electrical rating and UL/cUL Listed: 30 V DC, and 6 A, resistive; B300, pilot duty (B300 is a power limit specification for inductive loads) Voltage withstand: ± 36 V DC
Analogue multifunctional outputs 	Current output: <ul style="list-style-type: none"> Range: Any custom range between -25 to 25 mA DC Accuracy: 1 % of range Resolution: 16 bits (< 2 uA / bit) Type: Active output (internal supply) Load: Maximum ± 25 mA \rightarrow 400 Ω Voltage output: <ul style="list-style-type: none"> Range: Any custom range between -10 to 10 V DC Accuracy: 1 % of range Resolution: 16 bits ($< 0,7$ mV / bit) Load: Minimum ± 10V \rightarrow 600 Ω

Category	Specification
	<ul style="list-style-type: none"> Internal resistance, power ON: < 1 Ω Internal resistance, power OFF: > 10 MΩ <p>General information for all outputs:</p> <ul style="list-style-type: none"> Refresh rate (max): 50ms (input to output) Voltage withstand: ± 36 V DC
<p>Analogue multifunctional PWM outputs</p> 	<p>PWM output:</p> <ul style="list-style-type: none"> Frequency range: 1 to 2500 Hz ± 5 Hz Duty cycle accuracy (5 to 95 %): 0.5 % within reference temperature range Resolution: 12 bits (4096 steps) Voltage: Low level: < 0.5 V. High level: > adjustable 1 to 10 V. Maximum: 10.2 V Output impedance: 25 Ω <p>General information for all outputs:</p> <ul style="list-style-type: none"> Refresh rate (max): 50 ms (input to output) Voltage withstand: ± 36 V DC
<p>Digital inputs</p> 	<p>Negative or positive trigger inputs:</p> <ul style="list-style-type: none"> ON: -36 to -8 V DC, and 8 to 36 V DC OFF: -2 to 2 V DC <p>Minimum pulse length: 50 ms Impedance: 3.9 kΩ Voltage withstand: ± 36 V DC</p>
<p>Analogue multifunctional inputs</p> 	<p>Digital inputs with wire break detection:</p> <ul style="list-style-type: none"> Dry contact inputs, 3 V DC internal supply Wire-break detection with maximum resistance for ON detection: 100 Ω to 400 Ω <p>Current inputs:</p> <ul style="list-style-type: none"> From active transmitter: 0 to 20 mA, or 4 to 20 mA Accuracy: ± 10 μA ± 0.25 % of actual reading <p>Voltage inputs (DC):</p> <ul style="list-style-type: none"> Range: ± 10 V DC / 0 to 10 V DC Accuracy: ± 10 mV ± 0.25 % of actual reading <p>Resistance measurement inputs, 2 wire (RMI):</p> <ul style="list-style-type: none"> Resistance measurement: 0 to 4.5 kΩ Accuracy: ± 1 Ω ± 0.25 % of actual reading <p>Resistance measurement inputs, 1 wire (RMI):</p> <ul style="list-style-type: none"> Resistance measurement: 0 to 4.5 kΩ Accuracy: ± 2 Ω ± 0.25 % of actual reading <p>Pt100:</p> <ul style="list-style-type: none"> Range: -200 to 850 $^{\circ}$C Accuracy: ± 1 $^{\circ}$C ± 0.25 % of actual reading <p>Pt1000:</p> <ul style="list-style-type: none"> Range: -200 to 850 $^{\circ}$C Accuracy: ± 0.5 $^{\circ}$C ± 0.25 % of actual reading <p>Thermocouple type, range and accuracy:</p> <ul style="list-style-type: none"> E: -200 to 1000 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading) J: -210 to 1200 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading) K: -200 to 1372 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading) N: -200 to 1300 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading) R: -50 to 1768 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading) S: -50 to 1768 $^{\circ}$C (± 2 $^{\circ}$C ± 0.25 % of actual reading)

Category	Specification
	<ul style="list-style-type: none"> T: -200 to 400 °C (±2 °C ±0.25 % of actual reading) <p>Note: Twisted pair and shielded cable is recommended to achieve specification and optimisation of noise immunity.</p> <p>General information for all outputs:</p> <ul style="list-style-type: none"> Refresh rate (max): 50 ms (input to output) Voltage withstand: ±36 V DC All analogue multi-functional inputs have a common ground
Terminal connections	<p>Relay outputs: Terminals: Standard 45° plug, 2.5 mm² Wiring: 0.5 to 2.5 mm² (22 to 14 AWG), multi-stranded</p> <p>Other inputs: Terminals: Standard 45° plug, 1.5 mm² Wiring: 0.1 to 1.5 mm² (28 to 16 AWG), multi-stranded</p>
Torques and terminals	<p>Module faceplate screws: 0.5 N·m (4.4 lb-in)</p> <p>Connection of wiring to relay output terminals: 0.5 N·m (4.4 lb-in)</p> <p>Connection of wiring to digital input terminals: 0.25 N·m (2.2 lb-in)</p> <p>UL/cUL Listed: Wiring must be minimum 90 °C (194 °F) copper conductors only</p>
Galvanic isolation	<p>Between relay groups and other I/Os: 2210 V, 50 Hz for 60 s</p> <p>Between other input groups and other I/Os: 600 V, 50 Hz for 60 s</p>
Ingress protection	<p>Unmounted: No protection rating</p> <p>Mounted in rack: IP20 according to IEC/EN 60529</p>
Dimensions	L×H×D: 28 × 162 × 150 mm (1.1 × 6.4 × 5.9 in)
Weight	188 g (0.4 lb)

3. Legal information

3.1 Disclaimer and copyright

Open source software

This product contains open source software licensed under, for example, the GNU General Public License (GNU GPL) and GNU Lesser General Public License (GNU LGPL). The source code for this software can be obtained by contacting DEIF at support@deif.com. DEIF reserves the right to charge for the cost of the service.

General warranty

The warranty period for the purchased product is defined in the contract and order acknowledgement. In general, DEIF's Terms and Conditions of Sale and Delivery apply.

The product continuously monitors the operating temperature and stores this information in a log file on the device. DEIF uses this information for service purpose and to validate if issues with the product are covered by the warranty.

The software packages supplied are believed to be of the highest quality. Due to the nature of the software development process, it is possible that there are hidden defects in the software which may affect its use, or the operation of any software or device developed with this software package.

DEIF does not undertake responsibility for determining whether this package is suitable for the application, nor for ensuring the correct operation of the application software and hardware.

The warranty does not cover product wear parts, such as:

- Internal flash disc
- If applicable, SD card (purchased separately)
- Replaceable coil-cell battery, used for the real-time clock (available as a spare part)

Trademarks

DEIF and the DEIF logo are trademarks of DEIF A/S.

Bonjour[®] is a registered trademark of Apple Inc. in the United States and other countries.

Adobe[®], *Acrobat*[®], and *Reader*[®] are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

CANopen[®] is a registered community trademark of CAN in Automation e.V. (CiA).

SAE J1939[®] is a registered trademark of SAE International[®].

CODESYS[®] is a trademark of CODESYS GmbH.

EtherCAT[®], *EtherCAT P*[®], *Safety over EtherCAT*[®], are trademarks or registered trademarks, licensed by Beckhoff Automation GmbH, Germany.

VESA[®] and *DisplayPort*[®] are registered trademarks of Video Electronics Standards Association (VESA[®]) in the United States and other countries.

Google[®] and *Google Chrome*[®] are registered trademarks of Google LLC.

Linux[®] is a registered trademark of Linus Torvalds in the U.S. and other countries.

Modbus[®] is a registered trademark of Schneider Automation Inc.

Torx[®], *Torx Plus*[®] are trademarks or registered trademarks of Acument Intellectual Properties, LLC in the United States or other countries.

Windows[®] is a registered trademark of Microsoft Corporation in the United States and other countries.

All trademarks are the properties of their respective owners.

Copyright

© Copyright DEIF A/S. All rights reserved.

Disclaimer

DEIF A/S reserves the right to change any of the contents of this document without prior notice.

The English version of this document always contains the most recent and up-to-date information about the product. DEIF does not take responsibility for the accuracy of translations, and translations might not be updated at the same time as the English document. If there is a discrepancy, the English version prevails.