



DATA SHEET

kWh meter WQ2R96 MKII





DATA SHEET



kWh meter WQ2R96 MKII

- Accuracy class 1.0 (EN 62053-21)
- For single-phase and 3-phase networks
- Microprocessor-controlled meters with pulse output (SO)
- Simultaneous measurement of two quantities
- 60 to 400 V AC aux. power supply
- Complies with Electricity metering equipment standard (IEC 62052-11)



DEIF A/S · Frisenborgvej 33 · DK-7800 Skive
Tel.: +45 9614 9614 · Fax: +45 9614 9615
info@deif.com · www.deif.com

Document no.: 4921210165A

Application

The kWh meter type WQ2R96 MKII is intended for energy measurement in single-phase and 3-phase networks, providing a class 1.0 measurement of the imported or exported energy. The meter is microprocessor-controlled and equipped with two 7-digit electromechanical counters, which retain the reading in case of supply voltage failure. The meter also comes with one or two pulse outputs. The meter can be adapted to the applied current transformers.

WQ2R96 MKII Meter with two 7-digit registers and two pulse outputs for measurement of two types of energy (both kWh and kvarh imported or exported).

Technical specifications

Auxiliary voltage	60, 100, 230, 400 V AC ± 20 %
Rated frequency	45 to 65 Hz
Wire	Multi-stranded: 1.5 mm ² Single-stranded: 2.5 mm ²

Measuring specifications

Meas. voltage Un	Ph-N 400 V AC Ph-Ph 690 V AC, range ± 20 % Consumption: <0.1 VA per phase Overload capacity: 1.5 \times Un continuously 2 \times Un for 10 s
Meas. current In	-1 A or -5 A, range 0 to 1.6 \times In Consumption: <0.1 VA per phase Overload capacity: 3 \times In continuously 25 \times In for 3 s 50 \times In for 1 s
Meas. frequency	50/60 Hz, range 16 to 400 Hz
Accuracy	Energy: Active energy EN62053-21: Class 1. Reactive energy EN62053-23: Class 2

Output and counter specifications


Relay outputs	Max. 250 V (AC), max. 100 V (DC)
Contact rating	AC: 250 V - 6 A - 1500 VA (250 V AC - 6 A resistive AC load 100,000 operations) DC: 35 V - 6 A - 210 W (30 V DC - 6 A resistive load 500,000 operations) Pulse duration: 100 ms No. of outputs: 2
Electromechanical counter	7 digits, each 4 \times 1.2 mm 1 pulse per selected unit (for example kWh)
Relay pulse output	Selectable (1 to 4000) Max. pulses per hour: 4000 Pulse duration: 100 ms
Isolation	1000 V (AC) between open contacts 4000 V (AC) between coil and contacts

Type test specifications

Temperature	-10 to 55 °C (operating) -25 to 70 °C (storage)	IEC/EN 62052-11
Climate	Relative humidity ≤ 75 %	IEC/EN 62052-11
Vibration	3 to 13.2 Hz: 2 mm _{pp} 13.2 to 100 Hz: 0.7 g	IEC/EN 60068-2-6 & IACS UR E10

Shock	50 g, 11 ms, half sine Tested with 3 impacts in each direction in all 3 axes In total 18 impacts per test	IEC/EN 60068-2-27, test Ea
Safety	Installation cat. III 600 V/cat. II 300 V Pollution degree 2 Tested to 2210 volt	IEC/EN 61010-1 tested at 50 Hz, 1 min Each galvanic group tested to other galvanic groups and to protection earth
EMC		IEC/EN 62052-11 IEC/EN 60533 power distr. zone IACS UR E10 power distr. zone
Materials	All plastic parts are self-extinguishing	UL94 (V0)
Protection	Front: IP52 (IP54 optional by gasket) Housing/terminals: IP20	IEC/EN 60529
Approvals	See DEIF homepage for valid approval	www.deif.com

Connection diagrams




Terminals

Inputs/Quantities	Terminals
-------------------	-----------

Measuring inputs	AC current	IL1	CT1 (1-3) (k-l)
		IL2	CT2 (4-6) (k-l)
		IL3	CT3 (7-9) (k-l)
	AC voltage	UL1	2 (L1)
		UL2	5 (L2)
		UL3	8 (L3)
		N	11
Auxiliary power supply		+/ACL	13
		–/ACN	14
Output modules	Output	Out –1	15
		C–12	16
		Out –2	17

Dimensions in mm/auxiliary voltage/output connections



Order specifications

WQ2R96 MKII

Example:

Type	AUX	Connection	VT ratio	CT ratio	Counter(s)	Relay 1 (2)	Relay 2
WQ2R96	100	3W4	10,000/100 V	50/1 A	1p/MWh E*, 1p/MWh I*	1p/MWh	1p/MWh

* E = Exported energy

I = Imported energy

Due to our continuous development we reserve the right to supply equipment which may vary from the described



DEIF A/S, Frisenborgvej 33
DK-7800 Skive, Denmark
Tel.: +45 9614 9614, Fax: +45 9614 9615
E-mail: deif@deif.com, URL: www.deif.com

